


Delivering the **SPARK** that Moves the World

Ignition Cable with Silicone-Extruded Core **ISO 3808:2002 & SAE J2031 CLASS D**



① **Silicone-Extruded Core**

- Strength member composed of fiberglass or aramid fibers coated with conductive acrylic latex, with a layer of semi-conductive silicone extruded over the base core
- *Alternative: Strength member composed of conductive fiberglass with a layer of semi-conductive silicone extruded over the base core*

② **Insulation**

- Ethylene Propylene Diene Monomer (EPDM)

③ **Separator**

- Nylon Reinforcement Tape applied between Insulation and Jacket
- *Alternative: Fiberglass Braid applied between Insulation and Jacket*

④ **Jacket**

- Ethylene Vinyl Acetate (EVA)

Performance Characteristics

- Operating Temperature Range: -30°C to 180°C (-22°F to 356°F)
- Nylon Reinforcement Tape offers superior terminal retention characteristics
- Excellent RFI suppression characteristics in accordance with SAE J551/2

Industry Standards

- ISO 3808:2002, Class D, Type 3B
- SAE J2031, Class D, Type 3
- RoHS 2002/95/EC


Form of Delivery

- Non-returnable plywood reels

Ignition Cable with Silicone-Extruded Core

ISO 3808:2002 & SAE J2031 CLASS D

Cross-Sectional View



Double Extrusion

PRODUCT SPECIFICATIONS						
SILICONE-EXTRUDED CORE		CABLE				
Dimension "A"	Resistance @ 20°C (68°F) kΩ/ft (kΩ/m)	Dimension "B"	Dimension "C"	Min. Concentricity	Overall Diameter mm (in)	Strip Force 2" (51mm) lbs (N)
Diameter in (mm)		Insulation Min. Wall Thickness in (mm)	Jacket Min. Wall Thickness in (mm)			
.080 ± .008 (2.0 ± 0.2)	3 - 7 (9.8 - 23)	.06 (1.5)	.03 (0.8)	70%	7 ± 0.3 (0.276 ± 0.012)	5 - 15 (22 - 67)
.080 ± .008 (2.0 ± 0.2)	3 - 7 (9.8 - 23)	.08 (2.0)	.03 (0.8)	70%	8 ± 0.3 (0.315 ± 0.012)	5 - 15 (22 - 67)

Catalog Number	Wire Construction	Outer Jacket	Separator	Inner Insulation	Wire Size (mm)
75114	Double Extrusion (EVA/EPDM)	EVA	Nylon Tape	EPDM	7.0
75124	Double Extrusion (EVA/EPDM)	EVA	Fiberglass Braid	EPDM	7.0
85114	Double Extrusion (EVA/EPDM)	EVA	Nylon Tape	EPDM	8.0
85124	Double Extrusion (EVA/EPDM)	EVA	Fiberglass Braid	EPDM	8.0



4 Tesseneer Drive, Highland Heights, Kentucky 41076-9753

GENERAL CABLE is a trademark of General Cable Technologies Corporation.
©2008. General Cable Technologies Corporation. Highland Heights, KY 41076
All rights reserved. Printed in USA

Phone: (800) 438-7314
Fax: (859) 572-8470
Email: info@generalcable.com
www.generalcable.com
AUT-0083-1008