

Carol® Double Jacket Drill Cord

90°C, 600 Volt, MSHA Approved Remote Control & Drill Cord



Product Construction:

Conductors:

- 14 through 10 AWG fully annealed stranded bare copper
- ASTM B3/B174

Insulation

- Premium grade color coded 90°C EPDM
- Color Code: See chart below

Jacket

- 90°C, black, CPE or neoprene
- Temperature Range: -40°C to +90°C

Jacket Marking

- CPE jacket - CAROL (SIZE & NO. OF CONDS.) DOUBLE JACKET REMOTE CONTROL AND DRILL CORD 600 V 90C P-07-KA110003-MSHA MADE IN USA
- Neoprene jacket - CAROL (SIZE & NO. OF CONDS.) NEOPRENE DOUBLE JACKET REMOTE CONTROL AND DRILL CORD 600 V 90C P-07-KA110006-MSHA MADE IN USA

Applications:

- Industrial and light- to medium-duty mining applications
- Heavy-duty service as power supply cable
- AC systems (grounded and ungrounded)
- Heavy-duty and long service life applications
- Mobile and portable electrical equipment
- Motor and battery leads
- Wet or dry locations in underground mines in accordance with Schedule 26 of the U.S. Bureau of Mines
- 3-conductor cables – use on AC systems where no grounding is required or on DC systems with one conductor for grounding
- 4-conductor cables – use on two- or three-phase AC systems with one conductor used for grounding
- 5-conductor cables – use in applications where separating the system neutral from the frame ground is required

Features:

- Withstands severe environmental conditions
- Indent-printed for easy identification
- Withstands exposure to oil, acid, alkalines, heat, moisture and most chemicals
- Flexible stranding
- Excellent impact, crush and tear resistance
- Sunlight-resistant
- Reinforced jacket for increased durability

Industry Approvals:

- RoHS Compliant
- Passes MSHA Flame Test

Applicable Standards:

- ICEA S-75-381

Packaging:

- Lengths cut to order

CATALOG NUMBER	NO. OF COND.	AWG SIZE	COND. STRAND	NOMINAL COND. O.D.		NOMINAL INS. THICKNESS		NOMINAL O.D.		CURRENT AMPS ⁽¹⁾	APPROX. NET WT. LBS/M ⁽²⁾
				INCHES	mm	INCHES	mm	INCHES	mm		

CPE JACKET

02861	2	14	41/30	0.077	1.96	0.045	1.14	0.640	16.26	18	210
02862	3	14	41/30	0.077	1.96	0.045	1.14	0.670	17.02	18	240
02868	4	14	41/30	0.077	1.96	0.045	1.14	0.715	18.16	15	285
02835	5	14	41/30	0.077	1.96	0.045	1.14	0.785	19.94	12	345
02845	5	12	65/30	0.096	2.44	0.045	1.14	0.840	21.34	16	405
02806	6	12	65/30	0.096	2.44	0.045	1.14	0.890	22.61	16	470
02855	5	10	104/30	0.117	2.97	0.045	1.14	0.895	22.73	20	495

NEOPRENE JACKET

02961*	2	14	41/30	0.077	1.96	0.045	1.14	0.640	16.26	18	220
02962*	3	14	41/30	0.077	1.96	0.045	1.14	0.670	17.02	18	260
02968*	4	14	41/30	0.077	1.96	0.045	1.14	0.715	18.16	15	300
02935*	5	14	41/30	0.077	1.96	0.045	1.14	0.785	19.94	12	365
02945*	5	12	65/30	0.096	2.44	0.045	1.14	0.840	21.34	16	425
02906*	6	12	65/30	0.096	2.44	0.045	1.14	0.890	22.61	16	490
02955*	5	10	104/30	0.117	2.97	0.045	1.14	0.895	22.73	20	515

* Non-stock item; minimum quantity purchase required.

⁽¹⁾ Ampacities based on 90°C conductor and 30°C ambient temperature per Table 400.5(A)(1) of the National Electrical Code®.

⁽²⁾ Actual shipping weight may vary.

COLOR CODE CHART

NO. OF CONDUCTORS	COLOR**
3	Black, White, Green
4	Black, White, Red, Green
5	Black, White, Red, Green, Orange
6	Black, White, Red, Green, Orange, Blue

** Green conductor for grounding only.



4 Tesseneer Drive, Highland Heights, Kentucky 41076-9753

GENERAL CABLE and CAROL BRAND are registered trademarks of General Cable Technologies Corporation.

©2011. General Cable Technologies Corporation. Highland Heights, KY 41076 All rights reserved.

Printed in USA

Phone: 1.800.243.8020
1.859.572.8000
Fax: 1.859.572.9262
www.generalcable.com
Form No. CAR-0133-0211