

Lifetime Plus® Super Flex® Lighted Extension Cords

3 Conductor Grounded • Type SJTW • -50°C to 60°C • 300 Volts



CATALOG NUMBER	NO. OF COND.	AWG. SIZE	LENGTH OF CORD (FT)	COLOR OF JACKET	POWER RATING			PKG. PER CTN.	WT./UNIT LBS	WT./CTN. LBS	UPC CODE
					VOLTS	AMPS	WATTS				
03387.63.05	3	16	25	Yellow	125	13	1625	12	1.7	20	079407033874
03390.63.05	3	14	25	Yellow	125	15	1875	12	2.5	30	079407033904
03391.63.05	3	14	50	Yellow	125	15	1875	6	4.7	28	079407033911
03392.63.05	3	14	100	Yellow	125	13	1625	4	9.2	37	079407033928
03397.61.05	3	12	25	Yellow	125	15	1875	6	3.7	22	079407033973
03398.61.05	3	12	50	Yellow	125	15	1875	4	7.0	28	079407033980
03399.61.05	3	12	100	Yellow	125	15	1875	2	13.1	26	079407033997

Product Description:

Lifetime Plus® Super Flex® extension cords have a connector end that lights up to indicate the power is on. Twice as flexible as other extension cords, the high-visibility yellow cord resists moisture and will not crack in arctic cold or melt in desert heat. The super-tough jacket provides extra resistance to cracking and abrasion. The Lifetime Plus extension cords have a limited lifetime warranty and remain flexible to -50°C.

Product Construction:

Conductor:

- 14 AWG. or 12 AWG. stranded bare copper per ASTM B-174

Insulation:

- Premium-grade, color-coded PVC

Jacket:

- PVC; Yellow
- Temperature Range: -50°C to 60°C
- Voltage Rating: 300 Volts

NEMA Configuration:

- 5-15P/5-15R

Applications:

- Chain saws
- Wet/dry vacs
- Orbital sanders
- Other outdoor equipment

Features:

- Lights up with power
- Super-flexible
- Weather- and water-resistant
- Limited lifetime warranty
- 3-conductor grounded

Industry Approvals:

- UL Listed
- OSHA Acceptable