

# Low-Voltage Landscape Lighting Wire

60°C 150 Volts UL



## LOW-VOLTAGE LANDSCAPE LIGHTING WIRE - 150 VOLT - UL

CATALOG NUMBER	NO. OF COND.	AWG. SIZE	LENGTH OF CORD (FEET)	COND. STRAND	NOM. INS. THICKNESS		NOMINAL O.D.		POWER RATING <sup>(1)</sup>			PKG PER CTN.	APPROX. WEIGHT PER CTN. (LBS) <sup>(5)</sup>	CARTON DIMENSIONS (H x W x D)	UPC NUMBER
					INCHES	mm	INCHES	mm	VOLTS	AMPS	WATTS				
02309.66.01	2	16	50	26/30	0.045	1.14	0.155 X 0.296	3.94 X 7.52	150	19	2850	12	27	8.5 x 12.25 x 14	079407901531
02309.67.01	2	16	100	26/30	0.045	1.14	0.155 X 0.296	3.94 X 7.52	150	19	2850	12	44	9.5 x 14 x 17	079407901548
02309.18.01	2	16	500	26/30	0.045	1.14	0.155 X 0.296	3.94 X 7.52	150	19	2850	1	19	10.625 x 10.625 x 6.313	079407901567
02310.66.01	2	14	50	41/30	0.045	1.14	0.170 X 0.354	4.32 X 8.99	150	27	4050	8	25	8.5 x 12.25 x 14	079407901579
02310.67.01	2	14	100	41/30	0.045	1.14	0.170 X 0.354	4.32 X 8.99	150	27	4050	8	45	9.5 x 14 x 17	079407901586
02310.18.01	2	14	500	41/30	0.045	1.14	0.170 X 0.354	4.32 X 8.99	150	27	4050	1	37	10.625 x 10.625 x 8.25	079407901604
02311.18.01	2	12	500	65/30	0.045	1.14	0.190 X 0.385	4.83 X 9.78	150	36	5400	1	58	10.625 x 10.625 x 8.25	079407901611
02311.66.01	2	12	50	65/30	0.045	1.14	0.190 X 0.385	4.83 X 9.78	150	36	5400	8	30	8.5 x 12.25 x 14	079407113378
02311.67.01	2	12	100	65/30	0.045	1.14	0.190 X 0.385	4.83 X 9.78	150	36	5400	8	59	9.5 x 14 x 17	079407113385
02312.38.01	2	10	500	19/0234	0.045	1.14	0.400 X 0.200	10.16 X 5.08	150	47	7050	1	52	12 x 10 x 10	079407148160

<sup>(1)</sup> Amps and watts are offered ONLY as a guide to the end user.

<sup>(5)</sup> Actual shipping weight may vary.

### Product Construction:

#### Conductor:

- 12, 14 and 16 AWG. fully annealed stranded bare copper per ASTM B-3

#### Insulation:

- Premium-grade PVC, Black
- Duplex parallel design for easy tear-down during installation
- Polarity ridge on one leg for positive circuit identification
- Temperature Range: -20°C to +60°C

#### Jacket Marking:

- CAROL (SIZE) UNDERGROUND LOW ENERGY CIRCUIT CABLE SUNLIGHT RESISTANT FOR LOW VOLTAGE OUTDOOR LIGHTING E# (UL) -- CSA LL# LVLL 30V FT1

#### Applications:

- Low-voltage landscape lighting
- Low-voltage security lighting

#### Industry Approvals:

- UL Listed under a UL Miscellaneous Wire file
- UL Listed for outdoor applications
- UL Listed for direct-burial applications
- CSA approved
- RoHS Compliant

#### Packaging:

- Both 50' and 100' lengths are packaged in a sleeve
- 500' (513.4 m) spools
- Other put-ups available on special order